

HERITAGE DOOR SYSTEM	Alitherm Heritage	Alitherm Heritage 60	Sheerline Classic
Appearance	Authentic period steel look	Steel look	Heritage style
Authenticity compared to steel look	★★★★★	★★★★★	★★★★★
Typical use	Listed & conservation	Refurbishment, replacement & new build	Refurbishment , replacement & new build
Frame depth	47 mm	60 mm	64 mm
Max width single door	925 mm	925 mm	1026 mm
Max width French doors	1832 mm	1832 mm	2032 mm
Maximum PAS24 door width single door	925 mm	925 mm	1026 mm
Maximum PAS24 door width French door	1832 mm	1832 mm	2032 mm
Max standard door height single door	2100 mm	2100 mm	2300 mm
Max standard door height French door	2100 mm	2100 mm	2300 mm
Maximum PAS24 door height single door	2200 mm	2100 mm	2300 mm
Maximum PAS24 door height French door	2200 mm	2100 mm	2300 mm
Standard fixed sidelight sightline	33 mm	33 mm	48 mm
Standard door sash sightline single door	58 mm	67 mm	62 mm
Standard door sash sightline French door	58 mm	67 mm	62 mm
Standard door meeting style sightline French door	100 mm	116 mm	102 mm
Door sash PAS24 sightline single door	68 mm	67 mm	62 mm
Door sash PAS24 sightline French door	68 mm	67 mm	62 mm
Meeting style PAS24 sightline French door	117 mm	116 mm	102 mm
Handle block sightline single door	124 mm	133 mm	120 mm
Handle block sightline French doors	231 mm	248 mm	220 mm
Handle block sightline PAS24 single door	133 mm	133 mm	120 mm
Handle block sightline PAS24 French Door	248 mm	248 mm	220 mm
Opening options	In or out	In or out	In or out
Glazing thickness double glazed	28 mm	28 mm	28 mm
Glazing thickness triple glazed	28 mm	28 mm	28 mm
Overall U value double glazed single door	1.5 W/m ² K	1.4 W/m ² K	1.4 W/m ² K
Overall U value double glazed French door	1.4 W/m ² K	1.4 W/m ² K	1.4 W/m ² K
Overall U value triple glazed Argon Single door	1.4 W/m ² K	1.1 W/m ² K	1.1 W/m ² K
Overall U value triple glazed Argon French door	1.4 W/m ² K	1.1 W/m ² K	1.1 W/m ² K
Overll U value triple glazed Krypton	1.2 W/m ² K	1.2 W/m ² K	1.2 W/m ² K
Part Q PAS24 security	Optional upgrade	Standard - optional laminated glass	Standard - optional laminated glass
Part L compliant	Yes	Yes	Yes
Part F compliant	Yes	Yes	Yes
Weather testing	BS6375 tested	BS6375 tested	BS6375 tested

